

BT-THEATRE 250EZ

Mk2

B06038

DESCRIPTION

Very powerful 250Watt LED theater spot with electronic 14° to 54° zoom and excellent very low noise cooling.

FEATURES

- Extremely powerful LED theater spot with electronic zoom: 14° to 54° beam angle.
- The 250W warm white 3200K LED produces an incredible light output that easily outperforms traditional 2kW halogen theatre projectors!
- Excellent photometric characteristics: CRI / Ra >97, TLCI >98, CQS >94, Rf >93, Rg >100 !
- Color frame for use of color filters and eight-leaf barndoor included
- No more heavy and expensive dimmer packs needed!
- Reworked cooling system for extremely silent operation, low LED temperature and very stable light output.
- LCD-display to navigate easily through the reworked setup menu!
- DMX-controlled: 6 different channel modes (8bit and 16bit dimming) for maximum flexibility.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE ! (Briteq® code: 4645)
- Flicker free TV-recordings & no high-pitch dimmer noises, thanks to HF PWM dimming: up to 20kHz !
- Manual dimming & zoom/focus control: easy projector alignment on the stage + use on exhibition booths.
- The lamp behavior can be continuously adjusted from led to halogen.
- Four dimmer curves: linear, square, inverse square, S-curve
- In case of DMX failure, you can choose between blackout and freeze mode.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Lock function to avoid unwanted altering of the settings.
- Default factory settings + user settings can be saved/loaded.
- 3 & 5pin DMX in/outputs + Neutrik PowerCON in/outputs for easy daisy chaining.







www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2021 by BEGLEC NV. All rights reserved.

TECHNICAL SPECIFICATIONS

General : Application	Commercial, Stage & Rental, Theatre
General : Series	No
General : Weight (kg)	8.25
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	260
General : Color	black
General : Display	LCD
General : Fixation	M12
General : IP rating	indoor
Control : Modes	standalone, manual, DMX, DMX Master/Slave
Control : manual	Yes
Control : Master/Slave	Yes
Control : SMART-DMX	No
Control : Standalone	fixed
Control : programmable	No
Control : upgradable software	Yes
Control : maximum DMX channels	4
Light : lamp socket	none
Light : Lux	4700 @ 5 meter (beam 14°)
Light : lamp	COB
Light : min. color temperature (K)	3150
Light : max. color temperature (K)	3250
Light : CRI	97
Light : colors	Warm white
Light : mix colors	No
Light : functions	motorized zoom
Light : min. refresh rate (kHz)	No
Light : max. refresh rate (kHz)	No
Connections : input	3 pin XLR, 5 pin XLR, PowerCon®, usb, rdm, wireless DMX
Connections : output	3 pin XLR, 5 pin XLR, PowerCon®
Brand	BRITEQ
EANCode	5420025660389



www.briteq-lighting.com | <https://www.facebook.com/Briteq>

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2021 by BEGLEC NV. All rights reserved.