

PRO-1000SW

10" IN-WALL SUBWOOFER



DISCRETE LOW FREQUENCIES

A true subwoofer for both music and movies, the PRO-1000SW provides clean, dynamic, powerful low frequencies while its in-wall design keeps it hidden from view. Simple, easy-to-install design allows for direct, secure installation into a standard 16" OC stud bay using included wood screws for retrofit or new construction.

HIGH PERFORMANCE ACOUSTICS

10" long-throw Cerametallic™ woofer with reverse rolled surround provides dynamic, balanced, distortion-free low frequencies - all within a traditional stud bay. Maximize the output and acoustic performance using the KDA Series DSP amplifiers, which include presets for optimized EQ and limiter settings custom designed by Klipsch engineers specifically for the PRO-1000SW.

MDF ENCLOSURE

The durable, robust MDF enclosure, provides accurate, powerful low frequencies while helping to isolate sound from neighboring rooms.

FLAT, MAGNETIC GRILLE

Magnetic, bezel-free, paintable grille blends seamlessly into even the most luxurious of living spaces and home theaters.

SPECIFICATIONS	
FREQUENCY RANGE*	24Hz - 100Hz +/- 3dB
SYSTEM TYPE	Sealed Box
WOOFER	10" (25.4cm) Long-Throw Cerametallic™
MAXIMUM OUTPUT*	109dB @ 70Hz
POWER HANDLING	200W RMS / 500W Peak
IMPEDANCE	8 Ohm
ENCLOSURE MATERIAL	MDF
FINISH	Black Polymer Veneer with White, Paintable Grille
PRODUCT DIMENSIONS	22.0" x 17.63" x 4.0" (559mm x 448mm x 102mm)
MOUNTING DEPTH	3.4" (87mm)
CUTOUT DIMENSIONS	20.25" x 14.5" (514mm x 368mm)
PRODUCT WEIGHT	20.3 lbs (9.2 kg)
BUILT FROM	2017

* With Klipsch KDA Amplifier DSP Preset



3502 WOODVIEW TRACE INDIANAPOLIS, IN 46268 | KLIPSCH.COM