



Pro18sA

18" ACTIVE SUBWOOFER

-  Plywood Enclosure
-  Polyurea Coating
-  Built-in Amplifier
-  Easy Install

The Pro18sA is an active 18" Reflex Subwoofer engineered specifically for installation and portable solutions with a modern and trendy design to deliver high output and dynamics, extreme linearity and fidelity at a very competitive price, making them an affordable solution for the professional market. This subwoofer can be an ideal solution to use with Pro12A, Pro15A or MV12 for hotels, restaurants, bars, lounges, conference rooms, Djs and musicians among many others. Thanks to its 2000w Class D Amplifier, and you can control X- Over Frequency Adjustment (80Hz to 150Hz), Phase (0° or 180°) and Input Level, Output Signal. The Pro18sA can be connected between each other using the "Output" connector. A Line Output (Input Link) or Post X-Over Line Output can be selected. The cabinets are constructed using premium-quality 15mm plywood with polyurethane coating. Front and speakers' protection is assured by an acoustically transparent a powdercoated steel grill with acoustical foam. The Pro18sA professional active subwoofer was engineered to deliver powerful bass, providing enhanced headroom and a more defined audio experience with clear sound..

Product Type Active Reflex Subwoofer	Frequency Response (-6dB) 36Hz - 160Hz	Frequency / Type of X-Over Adjustable on the Back Panel from 80Hz to 150Hz
Amplifier Technology Class D Amplifier	Amplifier Power 1000W/2000W	Control Type X-Over Frequency Adjustment, Phase (0° or 180°), Input Level, Output Signal
Maximum SPL (calculated) 130dB/133dB (Half-Space)	Subwoofer Driver 1 x 18" (460mm), 4" (100mm) VC	Audio Signal Inputs Line Input
Input Connectors 1 x XLR / TRS combo	Audio Signal Outputs Line Output (Input Link) or Post X-Over Line Output	Output Connectors 1 x XLR
Protections RMS: 800W (550W + 250W) / Peak: 1400W	Operating Temperature Range 0°C - 40°C	Cooling Type Convection
Power Input AC 100V - 240V 50Hz/60Hz	Mains Connector Standard IEC socket	Power Consumption 380W
Fittings 1 x M20 and/or 35mm pole mount socket	Handles 2 on each Side	Grille Black Perforated Steel
Construction Heavily Braced Multi-laminate Birch Plywood	Finish Poliurea Coating	Dimensions (WxHxD) 560 x 545 x 780mm (22 x 21.5 x 30.7 in)
Net Weight 47.5kg (104.7lb)	Shipping Weight 54.5kg (120.2lb)	Accessories Transportation Dolly Individual Protective Cover