



The CM6QFT is the new contractors' reference: an easy to install speaker that reduces labor cost drastically.

The patented Quick-Fit system allows an installer to mount many speakers in a short time. On the CM6QFT, you will find factory-tightened clamps instead of screws. All one has to do is position the speaker in the ceiling, and release the 4 clamps by pushing their buttons with the round edge on the back of the (included) hex key. Dismounting the speaker is possible by turning the clamps 180 degrees with the hex key. Quick and easy: no more fumbling around with screws on top of a ladder!

This discrete and stylish loudspeaker has a 6 1/2" paper cone woofer that results in a very low distortion. To complete the sound, the CM6QFT has an integrated 1" tweeter. It makes the CM6QFT very suitable for paging calls and background music. The housing is made of high quality ABS. The grille is made of steel.

Standard color for the CM6QFT is white RAL9010. From 12 pieces on, the loudspeaker can be painted optionally in any other RAL color (REF: PAINTCM).

TECHNICAL SPECIFICATIONS

Type:	2 - Way HiFi
Woofer:	6.5" paper cone
Tweeter:	1" Soft Dome
Rated Power RMS:	6 W / 100Volt
Music Power RMS:	10 W / 100Volt
Rated Power RMS:	40 W / 16Ω
Music Power RMS:	60 W / 16Ω
Sound Pres. Level (SPL)	1W/1M : 91dB
Frequency range:	60 Hz - 20 kHz
Transformer power tapings:	6 - 3 - 1.5W
Dispersion @ 1-4-8 KHz:	180° - 80° - 45°
IP rating	50
Dimensions outside Ø:	237mm
Dimensions Cutout Ø:	216mm
Depth:	65mm
Ceiling thickness:	12.5 – 29mm
Weight:	1.1Kg
Grille:	steel
Grille removal tool:	included
Clamp release/tightening hex key:	included