WWW.LD-SYSTEMS.COM







The new LD Systems DAVE8XS is a portable and compact 2.1 multimedia system. It is equipped of a powerful 8" Bandpass subwoofer (150 W RMS) and 2×4 " + 1" silk dome satellites (2 x 100 W).

It delivers a crystal clear sound and was designed for all kinds of multimedia applications such as home recording, AV applications, DJ & Keyboard monitoring, PA for small sized public facilities (such as bars/pubs) etc. The A/B class amplification module integrated in the subwoofer delivers a high output and powers both sub and satellites. The LD DAVE 8XS features XLR and RCA Phono Line inputs, as well as all common protective circuits. The integrated limiter keeps your system safe from an overload and will guarantee a long operational life. On the side of the sub you will find an on/off switch, an 180° phase reverse and a separate subwoofer volume knob allowing you to find the perfect sound balance between crystal clear high tones, punchy mids and powerful bass. A "must-have" for all sound lovers with a great value for money!

- Max SPL: 117 dB
- Balanced Inputs
- Integrated amplification module
- Phase reverse
- Subwoofer volume control
- · Recessed thread for wall mounting
- 3/8" microphone stand adapter
- Front cover and wall mount brackets optional

SPECIFICATIONS LDDAVE8XS

Model name:	LDDAVE8XS
Туре:	Subwoofer: Band Pass / Satellite: Sealed
Subwoofer:	1 x 8" Custom Made
Satellites:	LF: 2 x 4" Custom Made HF: 1" Custom Made
Amplification:	Class A / B
Dispersion:	60° x 60°
Power Output (RMS):	Subwoofer: 150 W / Satellites: 2 x 100 W
Frequency Range:	45 Hz - 19 kHz
SPL (1 W / 1 m):	96 dB
Max SPL:	117 db
Protection:	Short circuit, Over-current, Limiter
Controls:	Volume, Sub Level, 180 ° Phase Reverse, On / Off Switch
Indicators:	Power
Subwoofer Connectors:	Input: Line: XLR, RCA Output: SPKn: Powered output for passive Satellites
Satellites Connectors:	Input: SPKn
Cooling system:	Heatsink
Power supply:	Transformer
Cabinet Material:	Subwoofer: 15 mm MDF / Satellites: 12 mm MDF
Cabinet Surface:	Painting
Dimensions (W x H x D):	Subwoofer: 352 x 430 x 434 mm / Satellites: 144 x 350 x 170 mm