

B08110

DESCRIPTION

 $2x\ 1500Wrms\ CLASS-TD\ amplifier\ (2x\ 2000Wrms\ @\ 2\Omega)$ with powerful low-frequency reproduction and crystal-clear high frequencies. Perfect for clubs, rental, theater, ...

FEATURES

- The SE-30000 power amplifier is unprecedented in terms of price / performance.
- The sophisticated design of this lightweight CLASS-TD amplifier ensures excellent and powerful low-frequency reproduction combined with crystal clear and delicately balanced high frequencies.
- Thanks to the big power reserve, excellent limiters and protections it can be used in all kinds of different applications such as discotheques, clubs, mobile audio, PA, rental, theater, ...
- The extremely high efficiency, reduced power waste and very low heat dissipation are the main advantages of this compact amplifier!
- The 2U enclosure weighs only 10 kg, which makes it perfect for mobile applications!
- The LCD-display shows: audio input level, mains voltage, working temperature and fan speed.
- Power output, stereo:
 - 2x 1000Wrms @ 8 Ω
 - 2x 1500Wrms @ 4 Ω
 - 2x 2000Wrms @ 2 Ω
- Power output, bridge:
 - 1x 3000Wrms @ 8 Ω
 - 1x 4000Wrms @ 4 Ω
- All the protections you can think of for professional use:
 - Inaudible signal + current limiter
 - overload protection
 - short circuit current protection
 - DC protection
 - thermal protection
 - AC/VHF protection
 - soft start
- Two FAN modes:Silent mode: minimum fan noise for use in recording studio, theatre, ...
 - Power mode: maximum cooling for use in rough conditions like discotheques, summer festivals, ...
- 3 different working modes: stereo, bridge mode, mono mode (inputs linked)
- Input sensitivity: 0,75V / 1,0V / 1,5 V
- Balanced in/outputs on XLR / COMBO
- 2 Speakon® compatible connectors (left, right & bridge outputs).









www.synq-audio.com | https://www.facebook.com/synq.audio/

Beglec NV has the right to change products and specifications with and without notice. Major as well as minor changes can be involved. This leaflet can contain errors, therefore we advice to consult your local dealer to ensure that actual features and specifications match your requirements. Copyright © 2021 by BEGLEC NV. All rights reserved.

TECHNICAL SPECIFICATIONS

General: Application DJ & Club, Stage & Rental

General: Series

General: Dimensions (cm) 48.2 x 8.8 x 36.5

General: Weight (kg) 10.06 **General: Color** black

General: Powerinput AC 230V, 50Hz

General: Energy Label Νo

General: Display LCD

General: Fixation 19" rack mountable

General: RU 2U **General: IP rating** indoor Audio: amplifier class TD Audio: min. frequency (Hz) 20 Audio: max. frequency (Hz) 20000 Audio: S/N ratio (> dB) 100 Audio: damping factor (>...) 800 Audio: max. output channels 2 Audio: Wrms 2Ω stereo, per 2000 channel

Audio : Wrms 4Ω stereo, per

channel

Audio : Wrms 8Ω stereo, per 1000

channel Audio: Wrms 4Ω bridge 4000 Audio: Wrms 8Ω bridge 3000

Audio: functions bridge mode, limiter


Connections: input 3 pin XLR, jack, PowerCon®

1500

Connections: output 3 pin XLR, speakon

Brand SYNQ

EA NCode 5420025681100



YOUR DEALER



