



Visit product page



FOS LUMINUS BAR IP65

L007376

IP 65 outdoor Battery operated LED bar, 24x4 watt RGBW 4in1 LED, 25 degrees, 0-100 dimmer, pixel control, Lithium Ion battery, 12 hours single color operation, IR remote and Wireless DMX, 103cm, DMX Channels: 6/8/14/50ch, true power con In/out.

TECHNICAL DETAILS

Product description

IP65 battery bar, suitable for outdoor events, wireless control, based on 24 RGBW LEDs, with 8-pixel control groups.

Light Source / Optics

Light sources: 24x RGBW LEDs, 4 watts each.
25-degree optics for each LED.

Effects

RGBW color mixing
Dimmer & strobe functions.
Pixel control with 8 LED groups.
Pre-programmed chases with adjustable speed.

Control

Wireless integrated DMX receiver, compatible with the AirLink transmitters.
Easy pairing with the press of a button.
DMX control with 6, 8, 14, and 50 channels.
Sound, Auto programs, and IR control are supplied with the fixture.
LED display for accessing the options menu.

Battery

Lithium ION battery, 12V, 27 Ah.

Approximate lifespan: 500 charging / discharging circles.

Charging time (full power): 6 hours.

Battery autonomy: 12 hours single color, ~4,5 hours full on.

Technical Specifications

Power supply: AC100/240 Volt, 50/60 Hz.

Power consumption: 100 Watt max.

Environment temperatures for operation: -20 to +40 degrees Celcius.

TruePowercon and 3pin DMX inputs & outputs.

Fixture dimensions: 102 x 7 x 8,5 cm (bar only), 107,5 x 11,2 x 17,5 cm (with the two mounting bases).

Weight: 5 Kgs

Packing dimensions (single fixture box): 25 x 17 x 114 cm

Gross Weight: 7Kgs

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FC-TP-PDC-3

Professional TruePowercon/ DMX cable for the Solo and Luminus P 3 meter.



FOS AirLink PRO

AirLink DMX transmitter



FOS AirLink 24

AirLink DMX transmitter/fader desk for the Solo a



FOS AirLink Foldable

AirLink DMX transmitter for the Solo / Luminus / N



FOS Case Luminus BAR IP65

Flight case with wheels for 6 pcs Luminus BAR IP6

