

# MTSUB12A

Amplified subwoofer - Bass reflex

**The perfect way to optimise your 10" and 12" speakers**

ref 10078

The MTsub12A offers precise, chestpounding basses at a 400 W RMS power output. It is compact, light and very resistant.

Its built-in active filter optimises the satellites output. Dedicated for installation and live performance.

- + Class D amplification
- + Stereo/mono XLR/RCA line input
- + Low-pass filter, and output signal filter
- + Light and compact – 21.6 kg

Rear



## COV-MT15

Protective cover

ref 10070

## COV-MT12

Protective cover

ref 9965

## COV-MT10

Protective cover

ref 9964



Protect your speakers from transport and time damages with our high quality covers.

Strong reinforced construction

You can access the preamplifier and the mounting socket while it is cover-protected

Direct access to the transport handles.

231

	MT15A	MT12A	MT10A	MTSUB12A
<b>Ref</b>	10025	9959	9958	10078
<b>RMS output</b>	400 W	300 W	180 W	400 W
<b>Max output</b>	800 W	600 W	360 W	800 W
<b>Bass output</b>	350 W RMS	250 W	150 W	400 W
<b>Treble output</b>	50 W RMS	50 W	30 W	-
<b>Amplifier class</b>	D + AB	D + AB	D + AB	D
<b>Pre-amplification</b>	MIC/LINE input - XLR-Jack combo	MIC/LINE input - XLR-Jack combo	MIC/LINE input - XLR-Jack combo	1 XLR and RCA Line stereo input
	1 Line/Aux input - Combo XLR-Jack and Mini Jack 3.5	1 Line/Aux input - Combo XLR-Jack and Mini Jack 3.5	1 Line/Aux input - Combo XLR-Jack and Mini Jack 3.5	
	XLR Line Out output	XLR Line Out output	XLR Line Out output	XLR Line Out output
	Volume control for each channel	Volume control for each channel	Volume control for each channel	Volume control for each channel
	General High/Low +/- 15 dB settings	General High/Low +/- 15 dB settings	General High/Low +/- 15 dB settings	Subwoofer cut-off frequency settings : from 80 - 180 Hz • Low-pass filter (OFF-80-125) for satellites output • Phase inverter 0-180
<b>Housing</b>	1 monitor-specific angle	1 monitor-specific angle	1 monitor-specific angle	Cubic housing with an integral protection grille
	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles	1 top and 2 side handles
	5 x M10 rigging points	4 x M10 rigging points	2 x M8 rigging points	
	36 mm socket for speaker stand	36 mm socket for speaker stand	36 mm socket for speaker stand	36 mm socket for speaker stand (on top)
<b>Dimensions (H x W x P)</b>	700 x 460 x 410 mm	595 x 385 x 348 mm	495 x 321 x 291 mm	469 x 489 x 360 mm
<b>Net weight</b>	18.4 kg	15.1 kg	10.2 kg	21.6 kg