

Product Detail Page



PA-900

Number: 17.1190

Mono PA mixing amplifier

- 1 x 120 W_{RMS}
- Silent operation due to fanless cooling concept
- 4 balanced mic/line inputs
- Mic 1 with priority circuit and automatic talkover
- Additional connection for desktop microphone via screw terminal
- 1 aux input
- Speaker outputs via screw terminals
- Line output
- Insert facility for preamplifier
- Input and output level controls
- 2-way tone control for the output
- 21 V phantom power, selectable
- Mains operation or 24 V emergency power operation
- Removable mounting brackets

Technical Facts

Output power	120 W _{RMS} , 160 W _{MAX}
Mic input	1.5 mV
Aux input	300 mV
Phono input	-
Speaker output	4 Ω , 70/100 V
Frequency range	50-15,000 Hz, ±3 dB
Equalizer bass	±10 dB/100 Hz
Equalizer midrange	-
Equalizer treble	±10 dB/10 kHz
S/N ratio	> 92 dB
THD	< 2 %
Power supply	230 V~/50 Hz/300 VA, 24 V = /9 A
Admiss. ambient temp.	0-40 °C
Dimensions	482x88x275 mm, 2 RS
Weight	10 kg
Special feature	
Inputs	
Microphone	4 x XLR
Aux, phono	1 x RCA L/R (aux)

