



Visit product page



IPA-CS

L005761

Ceiling Speaker (Quick-Mounting Type), 6.5" twin cone, 6W transformer, rated input 6w, 100/70V, 90dB spl. Frequency Response 100Hz-18kHz, white steel construction, ? 170 x 75H mm, Max Ceiling Thickness:25mm.

TECHNICAL DETAILS

Technical Specifications

Rated Input: 6W.

Max Input: 9W.

Impedance: 1.7k Ω , 3.3k Ω .

Power Taps: 100V: 6W, 3W \times 70V: 3 W, 1.5W.

SPL(1W /1m): 90dB.

MAX SPL(Rated /1m): 96dB.

Frequency Response(-10dB): 100Hz~18kHz.

Dispersion (4kHz / 1kHz): 55° / 160°.

Power Selecting Way: Three core cables: Blue 1.7k Ω , Red 3.3k Ω , Black: COM.

Material: Panel &Grille: Steel.

Color: White.

Temperature / Humidity: -20°C ~55°C; <95%.

Speaker Component: 6.5" Twin Cone Speaker.

Dimensions: Ø200 x 65H mm.

Mounting Hole: Ø 170 x 75H mm, Max Ceiling Thickness:25mm.


Weight: 0.7kg.

Mounting: Two Integral Spring-loaded Quick-Mounted locking Clamps.

Shipping Weight: 15kg, 20pcs.

Shipping Dimensions: 0.0669CBM, 42 x 37 x43 cm, 20pcs.

PHOTOS



www.fos-lighting.eu



