BT-THEATRE 261FC

DESCRIPTION

A powerful "6 in 1" FULL COLOR LED theater Fresnel with manual 15° \sim 50° zoom

FEATURES

- A powerful "6-IN-1" FULL COLOR LED theater Fresnel with manual $15^{\circ} \sim 50^{\circ}$ zoom.
- No more need for separate white and color projectors, BT-THEATRE 261FC does it all:
 - Perfect WHITE with high CRI > 93Ra and several CCT presets
 - Rich COLOR selection with color presets following the LEE® numbering!
- Thanks to the Color Calibration System, there are no more the color differences between different batches!
- Different CCT presets for white: 1800K, 3000K, 4000K, ..., 8000K.
- Very realistic redshift emulation during projector dimming.
- The 94 most used color presets (LEE® numbering) can be selected!
- The 200watt 6-color RGBALC-LED (Red, Green, Blue, Amber, Lime, Cyan) assures a very wide color gamut.
- Very silent operation: heat-pipe technology with low noise cooling fan and different presets (live, studio, ...).
- DMX-controlled: 10 different channel modes (1 to 21 channels) for maximum flexibility.
- Prepared for wireless DMX: just plug-in an optional WTR-DMX DONGLE!
- RDM-functionality for easy remote setup: DMX addressing, channel mode
- Flicker free TV-recordings thanks to the adjustable high LED-refresh rate!
- Four dimmer settings with different behavior & speed.
- Standalone mode: manual control for dimming, color/CCT presets, green/magenta shift & zoom.
- OLED-display to navigate easily through the setup menu!
- In case of DMX failure, you can choose between manual, blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Eight-leaf barndoor included.
- Rugged extruded aluminum housing.
- 3 & 5pin DMX in/outputs + PowerCON® compatible in/outputs for easy daisy chaining.









www.briteq-lighting.com | https://www.facebook.com/Briteq

TECHNICAL SPECIFICATIONS

General: Dimensions (cm) 39.2 x 22.3 x 33

General: Weight (kg)

General: Powerinput AC 100 - 240V, 50/60Hz

General: Energy Label No **General: Power consumption W** 230 **General**: Color black **General: Display OLED**

General: Fixation optional standard clamp

General: IP rating indoor

Control: Modes standalone fixed, manual, DMX

Control: Protocol DMX, Wireless DMX, RDM

Control: programmable Control: upgradable software Yes **Control: minimum DMX channels** 1 **Control: maximum DMX channels** 21 **Light: lamp socket** No **Light: lamp LED Light: min. color temperature (K)** 1800 **Light:** max. color temperature (K) 8000 Light : CRI 93

White, Amber, Lime, RGBALC **Light: colors**

Light: mix colors

Light: functions manual zoom, optional frost

Light: min. beam angle (°) 15 **Light**: max. beam angle (°) 50 **Light: max. refresh rate (kHz)** 25

3 pin XLR, 5 pin XLR, wireless DMX optional, PowerCon® or **Connections: input**

compatible

3 pin XLR, 5 pin XLR, PowerCon® **Connections: output**

or compatible **Brand BRITEQ**

EANCode 5420025660464



LUX (Full On) 54704	13676	6078	2188	855	547
BT-THEATRE 261FC					
BEAM: 14° FIELD: 28°	LIGIT	RESEA	я с н		
DISTANCE (m) 1 BEAM Ø (cm) 24 FIELD Ø (cm) 50	2 49 99	3 73 149	5 123 248	8 196 397	10 245 496









