
The series compromises 4 models, IB 8 with a 8" (1.5 in VC), IB12 with a 12" (2.95 in VC), IB15 with a 15" (4 in VC) and IB212 with 2x 12" (2.5 in VC) all equipped with rubber surround EU transducers to provide excellent power density in compact enclosures.

This INSTALL SUB series is the perfect partner to work with MOOSE INSTALL and LINEA series series acting as a supplement in PA installations to complete the existing sound with a deep and extended low frequency response, the ideal solution to any installed sound applications where space is limited allows close placement to any wall or corner.

The perfect solution for bars and restaurants, hotels, retail, etc.



Features:

- Bass reflex installation subwoofer
- Available in passive/active versions
- 1x 12" (2.95in VC) LF EU transducer
- 500W AES / 800W Program power
- 2x NL4 connectors in parallel
- Active version driven by class D amplifier, variable X-over frequency
- Versatile, compact to permit unobtrusive placement
- Supplied with wallmount brackets
- Rugged and durable 15mm birch plywood construction
- Powder coated custom perforated steel grille

● ● ● ●

450 [17.72]

460 [18.11]

Dimensions in mm [in]

Technical specifications:

Acoustical

Type Compact passive subwoofer

Enclosure design Bass reflex

Power rating (RMS/Program) 500W / 800W

Frequency range 38 - 160Hz (-10dB)

Nominal impedance 8 ohm

Transducer type 1x 12" LF (2.95in VC) EU transducer

Crossover frequency N/A

SPL (1W/1kHz) 129dB @ 1m (peak)
Connector 2x NL4 in parallel

Mechanical

Enclosure 15mm birch plywood, rugged polyurea coating
Grille Custom perforated metal grilles w/ acoustic foam

Color Black or white textured

Hardware 4 rubber feet

Wallmount brackets (optional)

Dimensions 460x450x360mm | 18.11x17.72x14.17in

Weight 21Kg | 46.30lb