



Visit product page

## FOS SUPERSTORM

L006796



IP65 led color strobe bar, Ultra-bright 144x5W cool white 7000K at 16-pixel segments, 242x2W RGBW at 32-pixel segments (2x16), DMX mode:13,64 and 89CH, Field angle: 90, 0-100 linear dimmer, 0.3 -20 pulse/ sec strobe , max 20Hz. Weatherproof seetronic power and XLR plugs, 700watt, 100 cm , 9kg.

### TECHNICAL DETAILS

#### Product description

LED Strobe bar, with RGBW and white LEDs, IP65, suitable for outdoor events as well. Easy linking system, and slide-in frost filter. It can be mounted with fixed omega brackets, or with adjustable angle ones, while multiple Super Storm bars can be mechanically linked & secured.

#### Light Source

144x cool white LEDs, divided into 16 segments. Type: 3535, 5 watts each.

242x RGBW 4 in 1 LEDs, in 32 segments. Type: 5050 SMD, 2 watts each.

Approximate lifespan: 50.000 h.

#### Effects

RGBW color mixing

White LED strobe effect, 20 Hz max.

Pixel control with 32 segments for RGBW, and 16 for the white strobe LEDs.

Clear view, or frosted light projection with the supplied slide-in frost.

#### Control

Master/Slave, stand-alone, and DMX control options.

3 DMX channel control modes: 13, 64 & 89 channels.

## Technical specifications

Power input: 100/240 Volt, 50/60 Hz.

Power consumption: 700 Watt max.

Aluminum housing construction with IP65 protection grade.

Suitable for temporary outdoor installations.

Touch menu buttons.

Operating temperatures: -20°C / + 40°C

Weight: 8,9 Kg.

Dimensions: 1000 x 181 x 88 mm.

## PHOTOS



## PRODUCT VIDEO



## ACCESSORIES



### FOS Case SuperStorm

Flight case with wheels for  
4 pcs strobe bars Supe



### FC-TP-PDC-1.5

Professional  
TruePowercon/ DMX cable  
1.5 meter.



### FC-TP-PDC-3

Professional  
TruePowercon/ DMX cable  
3 meter.



### FC-TP-PDC-5

Professional  
TruePowercon/ DMX cable  
5 meter.



### FOS SUPER CLAMP 200

Professional clamp for  
fixtures lifting weight 200

