

# HuddleSHOT®

Videoconferencing Camera with Integrated Audio

## ORDERING INFORMATION

### Black

999-50707-000 (North America)

999-50707-001 (Europe/UK)

999-50707-009 (Australia/New Zealand)

### Gray

999-50707-000G (North America)

999-50707-001G (Europe/UK)

999-50707-009G (Australia/New Zealand)

## OVERVIEW

The HuddleSHOT® All-in-One Conferencing Camera with integrated audio is Vaddio's newest solution optimized for huddle spaces. This USB conferencing product offers great performance, modern aesthetics and built-in IP management. HuddleSHOT provides professional 1080p/60 resolution for crisp, natural video and professional image – and its ultra-wide 125° horizontal FOV gets everyone in the picture.

HuddleSHOT is easy to deploy, easy to manage and easy to use. For huddle room users who need meetings to consistently start on time without any hiccups, the HuddleSHOT's plug and play simplicity makes it extremely easy to use. For AV and IT managers, Vaddio's intuitive browser-based user interface makes it simple to manage multiple HuddleSHOT cameras across multiple sites for easy enterprise deployments.

## FEATURES

- Two 10W speaker drivers optimized for full-bodied stereo audio
- Two integrated microphones pick up participant voices from up to 12 feet (3.6 meters) away
- For larger huddle spaces, expand coverage with TableMIC extension microphone
- Browser-based user interface makes it easy to manage many HuddleSHOT cameras across multiple sites for easy enterprise deployments
- HuddleSHOT can be set on a table, wall-mounted, or mounted to an AV cart with a variety of Legrand | AV mounting options available



## APPLICATION COMPATIBILITY

Compatible with any application that supports standard USB audio and video drivers, including but not limited to:

- Microsoft Skype for Business - Microsoft Skype™
- Microsoft Teams™
- Zoom®
- LogMeIn GoToMeeting®
- BlueJeans Network™
- Google Hangouts™ communication platform
- Amazon Chime™
- Cisco Webex®
- VidyDesktop™

## WHAT'S IN THE BOX?

Listed part numbers include the following items:

- HuddleSHOT camera in black or gray
- Bluetooth remote control
- AAA batteries, qty. 2
- PoE+ power injector with AC cord set(s)
- USB 3.0 Type A to Type C cable, 6 ft (1.8 m)
- Cat-5e cable, 10 ft (3 m)
- Wall mount with mounting hardware, black or white
- Quick-Start Guide

## TECHNICAL SPECIFICATIONS

Camera & Image	<b>Outputs/protocols</b>	USB 3.0, IP (H.264) RTMP or RTSP format
	<b>Aspect ratio</b>	USB: 16:9 (all resolutions) IP (H.264) Streaming: 16:9, 3:2 and 4:3
	<b>USB 3.0 (UVC) resolutions/frame rates</b>	1080p down to 180p at 60/30/15; automatically negotiated
	<b>Streaming resolutions/frame rates</b>	Simultaneous IP (RTSP or RTMP format with H.264 compression) up to 1080p down to 180p 1080p at 30/25/15; others 60/30/25/15
	<b>Image device</b>	1/1.9 Type CMOS Sensor
	<b>Pixels</b>	2.12 million
	<b>Lens/Zoom</b>	125° at 1x zoom with no video dewarp; 110° at 1x zoom with full video dewarp
	<b>Min. working distance</b>	250 mm
	<b>Min. illumination</b>	100+ lux recommended
	<b>Backlight compensation</b>	On / off
	<b>White balance</b>	Auto / Manual
	<b>S/N ratio</b>	More than 50 dB
	<b>Power</b>	PoE+
	<b>Remote management</b>	BLE Remote, web interface, Telnet
	<b>Presets</b>	Custom Home
	<b>Invertible</b>	No
<b>Warranty</b>	2 years. Option for purchasing additional 3 years	
Audio	<b>Microphone Input</b>	2-channel, 16-bit, 16 kHz sample rate
	<b>EasyMic Port</b>	RJ-45, 12V, bidirectional
	<b>IP Streaming</b>	2-channel (PCM), 16-bit resolution, 48 kHz sample rate
	<b>USB Streaming Record/Playback</b>	2-channel (UAC), 16-bit resolution, 48 kHz sample rate
	<b>Speaker Output</b>	2-channel (stereo), 16-bit, 48 KHz sample rate, 120-20000 Hz
Application Requirements	<b>Operating Systems</b>	Supporting Operating Systems - Windows 7, 8.1, 10 - MacOS 10.12, 10.13, 10.14
	<b>Audio and Video device drivers</b>	Support for standard audio and video device drivers - UAC 1.0 Audio - UVC 1.1/1.5 Video - HID 1.11
Physical & Environmental	<b>Weight</b>	5.25 lbs. (2.38 kg)
	<b>Height</b>	4.12 in. (10.5 cm)
	<b>Width</b>	24.0 in. (61 cm)
	<b>Depth</b>	3.7 in. (9.4 cm)
	<b>Operating/storage temperature</b>	0°C to +40°C (32°F to 104°F)
	<b>Operating/storage humidity</b>	20% to 80% RH, non-condensing
	<b>Country of Origin</b>	United States of America

Specifications are subject to change without notice.



THE ART OF EASY | [legrandav.com](http://legrandav.com)

**USA** P 800.572.2011 E [av.vaddio.support@legrand.com](mailto:av.vaddio.support@legrand.com)  
**EMEA** P +31.495.580.840 E [av.emea.sales@legrand.com](mailto:av.emea.sales@legrand.com)  
**APAC** P +852.2145.4099 E [av.asia.sales@legrand.com](mailto:av.asia.sales@legrand.com)

©2019 Legrand AV Inc. 190246 Rev A 8/19 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.



**COMMERCIAL BRANDS**

Chief | Da-Lite | Luxul | Middle Atlantic | Projecta | Vaddio